

SKU	PPU1

Grass Zone Yarn/Color **Grass Zone Denier**

Thatch Zone Yarn/Color

Thatch Zone Denier

Grass Zone Yarn Shape

Finished Pile Height

Finished Pile / Total Weight

Backing

Tuft Gauge

Tuft Bind

Permeability

Features

Test Data

TT

Nylon / Sport Green/Apple/Olive

4,200/8

Textured Diamond

3/8"

47 oz. / 84 oz.

13PP/18PET 2pt / 20oz. Embossed Rubber

3/16"

> 8 lbs.

HeatBlock **UV Stabilizers**

CAL 1350, ASTM D2859, ASTM E-108, ASTM E648, ASTM E84, EN-71

PRECISION PUTT[™] TRI

Tour-pro tested and TGL-approved, Precision Putt sets the gold standard for performance and durability. This nylon turf delivers true ball roll, consistent speed, and a natural, multi-colored appearance. With its durable fibers and embossed rubber backing, it excels in putting, receiving approach shots, and handling high-traffic areas like golf courses and TrampleZones™.



LIMITED LIFETIME WARRANTY



100% NYLON W/HEATBLOCK TECHNOLOGY



REALISTIC BALL CHECK AND ROLL WITH CHIP AND PITCH SHOTS



STIMP METER SPEED: 10-12















PRECISION PUTT TRI



Official Synthetic Surface

Primary Yarn Polymer	Nylon	
Yarn Cross Section	Textured Diamond	
Standard Color	Sport Green/Apple/Olive	
Fabric Construction	Tufted	
Second Yarn Polymer Thatch		
Secondary Yarn Color		

Primary Backing	13PP/18PET 2pt
Coating Type	20 oz. Embossed Rubber
PE Yarn Denier / Ends	4,200 / 8
Texturized Thatch Denier / Ends	
Warranty Period	Limited Lifetime

FINISH FABRIC	ENGLISH	ENGLISH SYSTEM	
Nominal Specification	Value	Units	Method
Pile Height (Nominal)	3/8	inches	D-5823
Face Weight	47	oz/yd²	D-5848
Total Fabric Weight	84	oz/yd²	D-5848
Primary Backing Weight	6	oz/yd²	D-5848
Secondary Coating Weight	20	oz/yd²	D-5848
Tuft Bind	> 8	lbs.	D-1335
Grab Tear Strength (Average)	> 200	lbs.	D-5034
Total Yarn Linear Density	4,200	Denier	D-1577
Elongation to Break	> 30	%	D-2256
Yarn Breaking Strength	> 20	lbs.	D-5793
Machine Gauge	3/16	inches	D-5793
Flammability	Passed		D-2859
Water Permeability	-		-
Fabric Width	15	ft	-

